



TECHNICAL DATA SHEET

Description:

OILWELL FLEXIBLE JACKET DETONATING CORD
80Grains/Ft-17Gms/mt. RDX – Low Shrink – Extra High Velocity

Denomination:

ETACORD 80 RDX LS XHV

Compounds

Explosive:	RDX	Color white/light grey
Textil:	Aramide Fiber	Color yellow
Jacket:	POLIAMYDE	Color brillant black

Characteristics

Temperature Resistance:	160°C / 1 Hr.
Shrincage:	1 % 160°C
Velocity of Detonation:	7500 Mts./Sec.
Lap Joint Sensitivity:	Yes
Outside Diameter:	5.3 mm ± 0,2 mm

Note: Not recommended for exposed use.

Packaging

UN Risk Clasification:	1.1 D	
UN Number:	0065	
Quantityper box:	152.4	Mts. (500 Ft.)
Gross Wt:	6.2	Kg.
Net Wt:	4.3	Kg.
NEC per box:	2.59	Kg.

Explosivos Tecnológicos Argentinos Sociedad Anónima (E.T.A. S.A.)
Ruta 25 Km 13 (Esq. Salta) Villa Rosa – Pilar – Bs. As.
Tel: +54 230 4494382/167/311
Fax: +54 230 4494165
www.etasa.com